



USB 3.0 **4-Port Portable Hub UH400** Highlights

- Connect up to 4 devices at a time
- Transfer speeds of up to 5Gbps
- Ultra compact design
- Built-in USB connector cable
- No driver required

Features



Connect up to 4 devices at a time

UH400 is perfect for anyone who has a computer with only one or two USB ports, and wants easier access to additional ports without having to switch between devices. UH400 gives users the freedom to connect up to 4 devices at a time.

Transfer speeds of up to 5Gbps

The 4 USB 3.0 ports support transfer speed of up to 5Gbps, 10 times faster than USB 2.0.It is also backward compatible with USB 2.0/1.1. The rapid transfer speeds of this device grants users full access to a highly functional data sharing highway.

Features

Ultra compact design



Ultra compact design

A highly portable device that comes in a compact, lightweight design. A nicely built compact sized makes it easier to store in your laptop pouch.



Built-in USB connector cable

A foldable cord design enables a more convenient way for storage or travelling.



No driver required

UH400 supports Plug and Play feature for devices running Windows 10/ 8.1 / 8 / 7 / Vista / XP or macOS and Linux systems.

Specifications

Basic

Dimensions:	2.8 x 2.8 x 0.7 in. (71 x 71 x 16.6 mm)	Certi
Output Interface:	4 USB 3.0 Ports	CE, F
Input Interface :	USB 3.0 Type-A	
Chipset:	VIA VL812 Chipset with Latest Firmware	Envir
System Requirements:	Windows (XP/Vista/7/8/8.1/10), macOS	• Ope
	(10.6/10.7/10.8/10.9/10.10/10.11) ,Linux OS	• Stor
Package Contents:	• USB 3.0 4-Port Portable Hub UH400	• Ope
	 Quick Installation Guide 	• Stor



For more information, please visit http://WWW.TP-LINK.COM/en/products/details/cat-4761_UH400.htm or scan the QR code on the left

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies CO., Ltd. Other brands and product names are trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

Others

tification: FCC, RoHS

ironment:

perating Temperature: $0^{\circ}C \sim 40^{\circ}C$ (32 °F $\sim 104^{\circ}F$) prage Temperature: $-40^{\circ}C \sim 70^{\circ}C$ (-40 °F $\sim 158^{\circ}F$) perating Humidity: $10\% \sim 90\%$ non-condensing prage Humidity: $5\% \sim 90\%$ non-condensing



USB 3.0 4-Port Portable Hub

